

# **RECOMMENDED FOR MID-SIZE ENTERPRISES**

### **BEST-OF-BREED SECURITY**

- Application-layer content inspection recognizes and blocks threats that stateful packet firewalls cannot detect.
- Powerful subscription-based security services boost protection in critical attack areas for multiple layers of defense. By partnering with leading technology providers, WatchGuard is able to integrate best-of-breed security components into one NGFW or UTM platform for stronger security at big cost savings.
  - APT Blocker uses a cloud-based sandbox with full system emulation to detect and block advanced malware and zero day attacks.
  - Application Control keeps unproductive, inappropriate, and dangerous applications off-limits.
  - Intrusion Prevention Service (IPS) delivers in-line protection from malicious exploits, including buffer overflows, SQL injections, and cross-site scripting attacks.
  - WebBlocker controls access to sites that host objectionable material or pose security risks.
  - Gateway AntiVirus (GAV) scans traffic on all major protocols to stop threats.
  - spamBlocker delivers continuous protection from unwanted and dangerous email.
  - Reputation Enabled Defense ensures faster, safer web surfing with cloud-based reputation look-up.
  - Data Loss Prevention (DLP) automatically inspects data in motion for corporate policy violations.
- Multiple VPN choices (IPSec, SSL, L2TP) for secure remote access include support for Android and Apple iOS devices.

#### **EASY TO MANAGE**

- Interactive, real-time monitoring and reporting at no additional charge give an unprecedented view into network security activity for immediate preventive or corrective actions.
- WatchGuard Dimension™, a public and private cloud-ready visibility solution, instantly turns raw data into security intelligence.
- Intuitive management console centrally manages all security functions.
- Drag-and-drop Branch Office VPN setup three clicks and your remote office is connected.

#### **HIGHEST UTM PERFORMANCE IN THE INDUSTRY**

- Firewall throughput of up to 6.7 Gbps and UTM throughput of 1.6 Gbps.
- No need to compromise protection for strong performance or vice versa. Multi-layered, interlocking security protects the network while throughput remains high.

### **HIGH PORT DENSITY**

- 8 Power over Ethernet ports make the M440 an ideal Gateway Wireless Controller for WatchGuard Access Points.
- 25 1 Gb Ethernet and 2 SFP+ Fiber ports eliminate the need for a separate switch. (SFP+ transceivers available as optional accessory.)
- Redundant power supplies ensure high availability. (Second power supply is an optional • accessory.)

#### MORE FLEXIBILITY IN NETWORK CONFIGURATIONS

atchGuard

Datasheet

Ideal for businesses that need greater flexibility in segmenting the network and securing wireless access points. Firebox M440 delivers high port density including both 1Gb and 10Gb connections, with full wire-speed bridging, plus Power over Ethernet (PoE) for direct connection of devices such as Wireless Access Points and IP phones.

#### NGFW AND UTM SOLUTIONS AVAILABLE

WatchGuard network security solutions easily integrate powerful security components to provide the protection your business needs. Whether you want a Next Generation Firewall (NGFW) or a full Unified Threat Management (UTM) solution, all security capabilities work together for a comprehensive approach to network protection with a single console for managing and reporting.



Firebox M440	TECHNICAL SPECIFICATIONS			
THROUGHPUT				
Firewall throughput	6.7 Gbps			
VPN throughput	3.2 Gbps			
AV throughput	2.2 Gbps			
IPS throughput	2.2 Gbps			
UTM throughput	1.6 Gbps			
Interfaces	25 1G copper (8 with PoE)			
	2 10G SFP+			
I/O interfaces	1 SRL/2 USB			
VLANs	400			
Concurrent connections (bi-directional)	4,000,000			
New connections per second	62,000			
Authenticated users limit	Unrestricted			
VPN TUNNELS				
Branch Office VPN	300			
Mobile VPN IPSec	300			
Mobile VPN SSL/L2TP	300			
SECURITY FEATURES				
Firewall	Stateful packet inspection, deep packet inspection, proxy firewall			
Application proxies	HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3			
Threat protection	DoS attacks, fragmented packets, blended threats and more			
VoIP	H.323, SIP, call setup and session security			
Filtering options	Browser Safe Search, YouTube for Schools			
Security subscriptions	Application Control, IPS, WebBlocker, GAV, Data Loss Prevention spamBlocker, Reputation Enabled Defense, APT Blocker			
VPN & AUTHENTICATION				
Encryption	DES, 3DES, AES 128-, 192-, 256-bit			
IPSec	SHA-1, SHA-2, MD5, IKE pre-shared key, 3rd party cert			
Single sign-on	Supports Windows, Mac OS X, mobile operating systems			
Authentication	RADIUS, LDAP, Windows Active Directory, VASCO, RSA SecurID, internal database			
MANAGEMENT				
Logging and notifications	WatchGuard, Syslog, SNMP v2/v3			
User interfaces	Centralized console (WSM), Web UI, scriptable CLI			
Reporting	WatchGuard Dimension includes 70 pre-defined reports, executive summary and visibility tools			
CERTIFICATIONS				
Security	Pending: ICSA Firewall, ICSA IPSec VPN			
Safety	NRTL/C, CB			
Network	IPv6 Ready Gold (routing)			
Hazardous substance control	WEEE, RoHS, REACH			
STANDARD NETWORKING				
QoS	8 priority queues, DiffServ, modified strict queuing			
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS			
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based			
Other features	Static routing, port Independence, transparent/drop-in mode			

Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right security solution for your network.

trebor u					8	Ŵ
	46	自意	(initiation)	mini		$(\Lambda \Lambda)$
Reset	LEDs	USB	Networ	k Interfaces		Power swi

	1	1:10	
	1		15
Cooling Fans		Power Supply	On/Off Switch

Product Dimensions	17″ x 15.25″ x 1.75″ (43 x 38 x 4.4 cm)		
Shipping Dimensions	18" x 21" x 5.25" (45.7 x 53.3 x 13.3 cm)		
Shipping Weight	18 lbs (8.2 Kg)		
AC Power	100-250 VAC Autosensing		
Power Consumption	U.S. 62 Watts (211.55 BTU/hr) (max) [optional redundant power supply available]		
Power over Ethernet	802.3at - 25W per port		
Rack Mountable	1U rack mount kit included		
ENVIRONMENT	OPERATING	STORAGE	
Temperature	32° F to 113° F 0° C to 45° C	-40° F to 158° F -40° C to 70° C	
Relative Humidity	10% to 85% non-condensing	10% to 95% non-condensing	
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)	
MTBF	65,000 hours at 77° F (25° C )		

## STRONG SECURITY AT EVERY LAYER

WatchGuard uses a best-of-breed strategy to create the most reliable security solutions on the market. By partnering with industry-leading technology vendors, WatchGuard delivers an all-star family of NGFW and UTM network security products.



To learn more about NGFW vs. UTM solutions and what your options are, visit www.watchguard.com/choice.

# **EXPERT GUIDANCE AND SUPPORT**

An initial subscription to LiveSecurity® Service is included with every Firebox M440 appliance. LiveSecurity provides hardware warranty with advance hardware replacement, technical support, and software updates.

### **MULTIPLE PURCHASE OPTIONS**

The flexibility of WatchGuard's integrated platform makes it easy to have exactly the security components your business network requires. Talk to your authorized WatchGuard reseller about very affordable bundled subscriptions for the Firebox M440.

www.watchguard.com

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895 www.watchguard.co No express or implied waranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2014 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Firebox, Fireware, and LiveSecurity are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE66834\_111714