



H3C S9820 Series

Data Center Switches

Release Date: October,2019



New H3C Technologies Co., Limited

H3C S9820 Series Data Center Switches

Product overview

H3C S9820 high-density intelligent switch series is developed for data centers and high-end campus networks. It provides powerful hardware forwarding capacity and abundant data center features. It provides up to 64*100G QSFP28 ports and 2 out-of-band management ports (one fiber port and one copper port). The 100G QSFP28 ports are 100G/40G autosensing and each QSFP28 ports can be split into four interfaces. This enables the switch to provide up to 128*25G/10G ports. The switch supports modular power modules and fan trays. By using different fan trays, the switch can provide field-changeable airflows. The switch is an ideal product for high-density 100GE or 40G switching and aggregation at data centers and cloud computing networks. It can also operate as a TOR access switch on an overlay or integrated network.

The S9820 switch series has one model:

- S9820-64H. The switch provides 64 × 100G QSFP28 ports, 2 × out-of-band management ports, 1 × mini USB port, 1 × USB port, 3 × fan tray slots, and 4 × power module slots. The switch uses 650W AC or DC removable power modules and supports 2+2 power module redundancy.



S9820-64H front panel



S9820-64H rear panel

Features and Benefits

High port density and powerful forwarding capacity

- The switch offers high-density 100G/40G/25G/10G ports and a forwarding capacity as high as 12.8 Tbps. By splitting one port into four ports, it can provide a maximum of 128 25G/10G ports. This enables the switch to provide high-density server access in high-end data centers without oversubscriptions.

Powerful SDN capacity

- The new-generation switching chip architecture greatly enhances the SDN capacity of the switch. IFP handles OpenFlow flow tables with more flexibility and resources. The switch supports exact match for ACLs to handle massive traffic on data center SDN networks.
- Supporting the standard OpenFlow protocol, the switch can be managed by an H3C VCF controller, a mainstream cloud management platform, or a third-party controller, which can provide flexible network customization and automated network management. Users or third-parties can use standard interfaces to develop and deploy dedicated network management polices to enable rapid service deployment and expansion and intelligent device management

Abundant data center features

The switch supports abundant data center features, including:

- EVB—Supports using Virtual Ethernet Port Aggregator (VEPA) to upload data traffic of VMs to physical switches connected to the server for processing.
- FCoE—Allows transmission of FC packets over Ethernet so that FC SAN services and LAN services can run over the same network infrastructure.
- PFC, ETS, and DCBX—Helps provide FC storage and high-performance computing services with low-latency and no data loss.
- VXLAN—The switch can operate as a high-performance VXLAN hardware gateway to support multitenant data center services. In conjunction with the H3C cloud management platform, the switch can be used to set up an agile, resilient, highly available high-performance Layer 2 network, with support for long-distance virtual machine mobility, data mobility, and business continuity.

H3C Intelligent Resilient Framework2 (IRF2)

H3C Intelligent Resilient Framework 2 (IRF 2) can virtualize multiple switches into one virtual switch and provides the following benefits:

- High scalability: With IRF2, plug-n-play device aggregation can be achieved by adding one or more switches into the IRF2 stack, enabling IRF2 stacking on the new device. New devices can be managed with a single IP, and upgraded at the same time to reduce network expansion cost.
- High reliability: The IRF2 patented 1:N backup technology allows each slave device in the IRF2 stack to serve as the backup of the master, creating control and data link redundancy, and uninterrupted layer-3 forwarding. This improves reliability, avoids unplanned business downtime, and serves to improve overall performance. When the master device fails, traffic remains uninterrupted.
- Load balancing: IRF2 supports cross-device link aggregation, allowing upstream and downstream to be connected to more than one physical link. This creates another layer of network redundancy, and boosts the network resource utilization.
- Availability: H3C S9820 switch series Implements IRF2 through standard Hundred Gigabit Ethernet (100GE) or 40 Gigabit Ethernet (40GE) ports. It can allocate bandwidth for business and application access, and reasonably splits local traffic and upstream traffic. IRF2 rules are obeyed within and across the rack, but also across the LAN. Multiple reliability protection

Multiple reliability protection

- The S9820 switch series provides multiple reliability protection at both switch and link levels. With over current, overvoltage, and overheat protection, all models have a redundant pluggable power module, which enables flexible configuration of AC or DC power modules based on actual needs. The entire switch supports fault detection and alarm for power supply and fan, allowing fan speed to change to suit different ambient temperatures.
- The switch supports diverse link redundancy technologies such as H3C proprietary RRPP, VRRPE, and Smart Link. These technologies ensure quick network convergence even when large amount of traffic of multiple services runs on the network.

Abundant QoS features

The switch provides abundant QoS features, including:

- H3C S9820 switch series supports Layer 2 to Layer 4 packet filtering, which can provide traffic classification based on source MAC address, destination MAC address, source IP address, destination IP address, TCP/UDP port number, protocol type, and VLAN.
- Each 100G port provides a flexible queues scheduling algorithm, which can be set based on ports and queues at the same

time.

- S9820 switch series supports five queuing modes include SP (Strict Priority), WRR (Weighted Round Robin), SP+WRR, WFQ, and SP+WFQ.
- S9820 switch series supports CAR (Committed Access Rate) function with a minimum granularity of 8Kbps, and port mirroring on both directions used to monitor packets on the specified port and forward the packets to the monitoring port for network detection and troubleshooting.
- The special XPE buffer structure in the switching chips allows the system to balance packets to the inbound or outbound port. This avoids buffer congestion on a single port and improves buffer usage efficiency.

Outstanding management capacity

- Provides multiple management interfaces, including the console port, mini USB port, USB port, and two out-of-band management ports.
- Supports configuration and management from CLI or a mainstream network management platform and H3C IMC Intelligent Management Center.
- Supports multiple access methods, including SNMPv1/v2c/v3, Telnet, SSH 2.0, SSL, and FTP.
- Supports standard NETCONF APIs that allow users to configure and manage the switch, enhancing the compatibility with third-party applications.
- Provides a variety of traffic monitoring and analytic tools, including sFlow, NetStream, SPAN/RSPAN/ERSPAN mirroring, and port mirroring to help customers perform precise traffic analysis and gain visibility into network application traffic. With these tools, customers can collect network traffic data to evaluate network health status, create traffic analysis reports, perform traffic engineering, and optimize resource allocation.
- Supports realtime monitoring of buffer and port queues, allowing for visible and dynamic network optimization.
- Supports PTP (Precision Time Protocol) to achieve highly precise clock synchronization.

Flexible choice of airflows

- To cope with data center cooling aisle design, the H3C S9850 switch series comes with flexible airflow design, which features bi-cooling aisles in the front and back. Users may also choose the direction of airflow (from front to back or vice versa) by selecting a different fan tray.

Comprehensive security control policies

- H3C S9820 switch series supports AAA, RADIUS and user account based authentication, IP, MAC, VLAN, port-based user identification, dynamic and static binding; when working with the H3C iMC platform, it can conduct real time management, instant diagnosis and crackdown on illicit network behaviors
- H3C S9820 switch series supports enhanced ACL control logic, which enables an enormous amount of in-port and out-port ACL, and delegate VLAN based ACL. This simplifies user deployment process and avoids ACL resource wastage.
- S9820 switch series can also take advantage of Unicast Reverse Path Forwarding (Unicast RFP). When the device receives a packet, it will perform the reverse check to verify the source address from which the packets are supposedly originated, and will drop the packet if such path doesn't exist.

Hardware Specification

Item	S9820-64H
Dimensions (H × W × D)	88.1× 440 × 540 mm (3.44 × 17.32 × 21.26 in)
Weight	≤ 18 kg (39.68 lb)
Console port	1
Out-of-band management port	One GE copper port and one GE fiber port

Mini USB port	1
USB port	1
Flash/SDRAM	4GB/8GB
QSFP28 port	64
Expansion slot	N/A
AC-input voltage	90 VAC to 264 VAC
DC-input voltage	-40 VDC to -72 VDC
Power module slot	4
Fan tray slot	3
Air flow direction	From front to rear or from rear to front
Static power consumption	Dual AC: 336W
Typical power consumption	Dual AC: 519W
Operating temperature	0°C to 45°C (32°F to 113°F)
Operating humidity	10% to 90%, noncondensing

Software Specification

Item	Specification
Line-rate switching	Switching capacity 12.8 Tbps
	Forwarding capacity 4400 Mpps
Forwarding mode	Store-forward and cut-through modes
Virtualization	IRF2
	Distributed device management, distributed link aggregation, and distributed resilient routing
	Using standard Ethernet interfaces for IRF connection Setting up an IRF fabric by using IRF member devices in the same site or geographically dispersed
Link aggregation	10GE/25GE/40GE/100GE port aggregation
	Static aggregation, dynamic aggregation
Data center	VXLAN, VXLAN EVPN
	802.1Qbb PFC, 802.1Qaz ETS, ECN
	EVB: VEB, VEPA, Muti-channel
	OpenFlow 1.3.1
	NETCONF, Python Service chain Multiple types of OpenFlow controllers
Jumbo Frame	Supported
MAC address table	Static MAC address
	Blackhole MAC address
VLAN	Port-based VLAN (quantity: 4094)
	Default VLAN

Item	Specification
Traffic monitoring	sFlow/NetStream
DHCP	DHCP server/client DHCP snooping/DHCP relay DHCP snooping support for Option 82/DHCP relay agent support for Option 82
ARP	Gratuitous ARP Dynamic ARP inspection ARP anti-attack ARP source-suppression ARP detection
IP routing	Static routing, RIPv1/v2, OSPFv1/v2/v3, BGP, IS-IS ECMP, VRRP, policy-based routing BGP4+ for IPv6, VRRP, IPv6 policy-based routing
IPv6	IPv6 ND IPv6 PMTU ICMPv6, Telnetv6, SFTPv6, SNMPv6, BFDv6, VRRPv3 IPv6 portal/IPv6 tunnel
Multicast	IGMP snooping v2/v3 IGMPv1/v2/v3 PIM-DM/SM IPv6 PIM-DM/SM/SSM Bi-directional -PIM, MSDP MLD snooping Multicast policy
Zero-configuration	Auto-config
MPLS	MPLS L3VPN
MSTP	STP/RSTP/MSTP PVST+/RPVST+ STP Root Guard BPDU guard
QoS/ACL	Inbound and outbound traffic rate limit CAR Eight output queues on each port Flexible port-and queue-based queuing and scheduling algorithms SP, WRR, WFQ, SP+WRR, and SP+WFQ queuing 802.1p and DSCP priority re-marking Packet filtering at Layer 2 to Layer 4 Traffic classification based on source MAC address, destination MAC address, source IPv4/IPv6 address, destination IPv4/IPv6 address, port number, protocol type, and VLAN Time range WRED

Item	Specification
Mirroring	Traffic mirroring N:4 port mirroring Local port mirroring, remote port mirroring
Security	Hierarchical user management and password protection AAA /RADIUS/HWTACACS SSH 2.0 IP address+MAC address+port number binding IP source guard HTTPs/SSL PKI 802.1X MAC authentication EAD
Loading and upgrading	Loading/upgrading through the XMODEM protocol Loading/upgrading through FTP and TFTP
Management and maintenance	Configuration via CLI, Telnet, and Console port Scheduled job IRF-based ISSU SNMPv1/v2c/v3 IMC System logs Hierarchical alarms NTP, SNTP Power, fan and temperature alarms Debugging information output Ping and tracert File uploading and downloading through the USB port
EMC	FCC Part 15 Subpart B CLASS A ICES-003 CLASS A VCCI CLASS A CISPR 32 CLASS A EN 55032 CLASS A AS/NZS CISPR32 CLASS A CISPR 24 EN 55024 EN 61000-3-2 EN 61000-3-3 ETSI EN 300 386 GB/T 9254 YD/T 993
Safety	UL 60950-1 CAN/CSA C22.2 No 60950-1

Item	Specification
	IEC 60950-1
	EN 60950-1
	AS/NZS 60950-1
	FDA 21 CFR Subchapter J
	GB 4943.1

Order information

PID	Description
LS-9820-64H	H3C S9820-64H L3 Ethernet Switch with 64 QSFP28 Ports
Power	
LSVM1AC650	650W AC Power Supply Module
LSVM1DC650	650W DC Power Supply Module
Fan	
LSWM1BFANSCB	Fan Module with Port to Power Airflow
LSWM1BFANSC	Fan Module with Power to Port Airflow
Module	
LSWM18CQ	H3C S6820 8-Port QSFP28 Ethernet Optical Interface Module
LSWM124TG2H	H3C S6820 24-Port SFP28 and 2-Port QSFP28 Ethernet Optical Interface Module
Transceiver	
SFP-FE-SX-MM1310-A	100BASE-FX SFP Transceiver, Multi-Mode (1310nm, 2km, LC)
SFP-FE-LX-SM1310-A	100BASE-LX SFP Transceiver, Single Mode (1310nm, 15km, LC)
SFP-FE-LH40-SM1310	100BASE-LH40 SFP Transceiver, Single Mode (1310nm, 40km, LC)
SFP-GE-T	1000BASE-T SFP
SFP-GE-SX-MM850-A	1000BASE-SX SFP Transceiver, Multi-Mode (850nm, 550m, LC)
SFP-GE-LX-SM1310-A	1000BASE-LX SFP Transceiver, Single Mode (1310nm, 10km, LC)
SFP-GE-LH40-SM1310	1000BASE-LH40 SFP Transceiver, Single Mode (1310nm, 40km, LC)
SFP-GE-LH40-SM1550	1000BASE-LH40 SFP Transceiver, Single Mode (1550nm, 40km, LC)
SFP-GE-LH80-SM1550	1000BASE-LH80 SFP Transceiver, Single Mode (1550nm, 80km, LC)
QSFP-40G-LR4-WDM1300	40GBASE-LR4 QSFP+ Optical Transceiver Module
QSFP-40G-CSR4-MM850	QSFP+ 40GBASE Optical Transceiver Module (850nm,300m,CSR4,Support 40G to 4*10G)
QSFP-40G-SR4-MM850	QSFP+ 40GBASE Optical Transceiver Module (850nm,100m,SR4,Support 40G to 4*10G)
QSFP-40G-BIDI-SR-MM850	QSFP+ 40GBASE BIDI Optical Transceiver Module (850nm,100m,SR)
QSFP-40G-LR4L-WDM1300	QSFP+ 40GBASE Optical Transceiver Module (1310nm,2km,LR4L,LC)
QSFP-40G-LR4-PSM1310	QSFP+ 40GBASE Optical Transceiver Module (1310nm,10km,MPO/APC,LR4,Parallel Single Mode)
QSFP-100G-SR4-MM850	100G QSFP28 Optical Transceiver Module (850nm,100m OM4,SR4,MPO)
QSFP-100G-PSM4-SM1310	100G QSFP28 Optical Transceiver Module (1310nm,500m,PSM4,MPO/APC)
QSFP-100G-LR4L-WDM1300	100G QSFP28 Optical Transceiver Module (1310nm,2km,LR4L,CWDM4,LC)



PID	Description
Cable	
LSWM1QSTK0	40G QSFP+ Cable 1m
LSWM1QSTK1	40G QSFP+ Cable 3m
LSWM1QSTK2	40G QSFP+ Cable 5m
LSWM1QSTK3	40G QSFP+ to 4x10G SFP+ Cable 1m
LSWM1QSTK4	40G QSFP+ to 4x10G SFP+ Cable 3m
LSWM1QSTK5	40G QSFP+ to 4x10G SFP+ Cable 5m
QSFP-100G-D-CAB-1M	100G QSFP28 to 100G QSFP28 1m Passive Cable
QSFP-100G-D-CAB-3M	100G QSFP28 to 100G QSFP28 3m Passive Cable
QSFP-100G-D-CAB-5M	100G QSFP28 to 100G QSFP28 5m Passive Cable
QSFP-100G-4SFP-25G-CAB-3M	100G QSFP28 to 4x25G SFP28 3m Passive Cable
QSFP-100G-4SFP-25G-CAB-1M	100G QSFP28 to 4x25G SFP28 1m Passive Cable



The Leader in Digital Solutions

New H3C Technologies Co., Limited

Beijing Headquarters
 Tower 1, LSH Center, 8 Guangshun South Street, Chaoyang
 District, Beijing, China
 Zip: 100102
 Hangzhou Headquarters
 No.466 Changhe Road, Binjiang District, Hangzhou, Zhejiang,
 China
 Zip: 310052
 Tel: +86-571-86760000

Copyright ©2019 New H3C Technologies Co., Limited Reserves all rights

Disclaimer: Though H3C strives to provide accurate information in this document, we cannot guarantee that details do not contain any technical error or printing error. Therefore, H3C cannot accept responsibility for any inaccuracy in this document. H3C reserves the right for the modification of the contents herein without prior notification

<http://www.h3c.com>